


Base plate size



Specifications

Application: Urban roads and street , Squares areas, Pedestrian areas, Residential areas,Parks

Installing Hight: 3-5m

Lamps: LED tube or Fluorescent lamp,30w-150w

Lamp Wattage: 2.5m pole:900mm light 3*10w T5 led or 3*21w T5 FL
 3m pole:1200mm light ,3*14w T5 led or 3*28w T5 FL
 3.5m pole:1200mm light ,3*14w T5 led or 3*28w T5 FL

Input Voltage: 220-240V/50Hz,110-130V/60Hz

Material: Aluminium body

Lighting Column: Three pieces extrude aluminium assembled trigon column (stripe surface), four aluminium bar supporting lampshade, powder coating

Lens: Clear acrylic /PC lampshade,

Color: Standard color are Black,Dark grey RAL7016 or Light grey RAL 7042 ,other colors are available

Standards:

Isolation degree Class I, IP Rating IP54

Ordering Information

Order No.	Lamp Wattage	Lamp Socket	Install Height	Gross/ Net Weight	Dimension L*W*H(cm)	Packing size(cm)	QTY(pcs) 20'/40'GP
HA0003D-2.5	T5,LED or FL	G5	2.5m	16/15kg	20x20x250	22x22x250	160/320
HA0003D-3.0	T5,LED or FL	G5	3.0m	19/18kg	20x20x300	22x22x300	80/240
HA0003D-3.5	T5,LED or FL	G5	3.5m	22/21kg	20x20x350	22x22x350	80/240