

Specifications

Application: Urban roads and street , Squares areas, Pedestrian areas, Residential areas,Parks

Installing Hight: 3-5m

Mounting : Post-top, suitable for Ø60,Ø76mmx100mm tenon

Lamps: LED modules

Lamp Wattage: 35W/ 65W/ 90W LED

Input Voltage : 90-270V AC,50/60Hz

Power Factor : >0.9 Luminous Flux : 100lm/W

LED Chips Brand : Cree,OSRAM,Philips,Bridgelux

LED Driver Brand : MEAN WELL,MOSO,INVENTRONICS

Color Temperature(CCT) : 3000K,4000K,5000K,6500K

Color Rending Index(CRI) : CRI>70

Beam Angel : 120x60°

Working Temperature : -40 to 50°C

Working Lifetime : 50000 hours

Material: AL, Aluminium body

Housing: Die cast aluminium,Polyester powder coating

Heat Sink: Die cast aluminium,

Lens: High efficiency acrylic refractor,

Color: Standard painting colors is black (BK) , dark grey(GY)


RAL7016 ,light grey(LG)(RAL7042),other color are available

Standards:

Isolation degree Class I, IP Rating IP65

Photometrics

TypeV Photometric curve



Lamp:90W LED

Ordering Information

Order No.	Lamp Wattage	LED chips Qty/Brand	Luminous Flux /Current If	Install Height	Gross/Net Weight	Dimension L*W*H(cm)	Packing L*W*H(cm)	QTY(pcs) 20'/40'GP
HA0024-35-BR	35W	30pcs/Bridge	3600lm/350mA	3m-5m	8kg /7kg	62x62X40	64x64x43	150 /300
HA0024-65-CR	65W	30pcs/CREE	6750lm/700mA	3m-5m	8kg /7kg	62x62X40	64x64x43	150 /300
HA0024-90-CR	90W	40pcs/CREE	9000lm/700mA	3m-5m	8kg /7kg	62x62X40	64x64x43	150 /300