



**Specifications**

**Application:** Urban roads and street , Squares areas, Pedestrian areas, Residential areas,Parks

**Installing Hight:** 2-3m

**Lamps:** LED tube or Fluorescent lamp,20w-60w

**Lamp Wattage:** Top lamp is CFL 23w or 70W HPS /MH  
 2.5m pole:900mm light ,2\*10w T5 led or 2\*21w T5 FL  
 3.0m pole:1200mm light ,2\*14w T5 led or 2\*28w T5 FL

**Input Voltage:** 220-240V/50Hz,110-130V/60Hz

**Material:** Aluminium body

Lighting top: Die cast aluminium,

Lighting Column: Four pieces extrude aluminium, Polyester powder coating

Lens: Clear arcylic lampshade for top lamp, Opal arcylic lampshade for column,

Color: Standard color are Black,Dark grey RAL7016 or

Light grey RAL 7042 ,other colors are available

**Standards:**

Isolation degree Class I, IP Rating IP54

**Ordering Information**

Order No.	Lamp Wattage	Lamp Socket	Install Height	Gross/ Net Weight	Dimension L*W*H(cm)	Packing size(cm)	QTY(pcs) 20'/40'GP
HA0002B-2.5	T5,LED or FL	E27/G5	2.5m	21/20kg	25x15x250	27x18x250	160/320
HA0002B-3.0	T5,LED or FL	E27/G5	3.0m	25/24kg	25x15x300	27x18x300	80/240