


Photometrics



Lamp:50W LED 5000Lm

**Application:** Urban roads and street , Squares areas, Pedestrian areas, Residential areas,Parks  
**Installing High:** 3-5m  
**Mounting :** Post-top: suitable for Ø76mmx80mm tenon  
**Lamps:** HID (HPS MH)/ LED bulb / CFL lamps, 30W-150W  
 70W/150W HPS high pressure sodium, cap: E27/E26/E40/E39  
 70W/150W MH metal halide, cap: E27/E26/E40/E39  
 30W/40w/50W Led bulb, cap: E27/E26/E40/E39  
 35W/45W/65W Compact fluorescent, cap: E27/E26  
**Input Voltage:** 90-270VAC,50-60HZ  
**Material:** Aluminium body  
 Housing: Die cast aluminium, Powder coating  
 Globe : High efficiency acrylic refractor  
**Color:** Standard color are Black,Dark grey RAL7016 or Light grey RAL 7042 ,other colors are available  
**Standards:**  
 Isolation degree Class I, IP Rating IP65



**Ordering Information**

Order No.	Lamp Wattage	Lamp Socket	Install Height m	Gross / Net Weight(kg)	Dimension L*W*H(cm)	Packing size(cm)	QTY 20'/40'GP
HA0007	MAX 150W	E27/E40	3m-5m	9 / 7	54x54X81	56x56x84	108/216