

SPECIFICATIONS:

Application: Urban roads and street , Squares areas, Pedestrian areas, Residential areas, Parks, Garden Installing Hight: 3m-5m

PS06B pole: high-tensile carbon steel, 90mm round straight non-tapered shaft, welded togher with an 165 mm round straight high-tensile carbon-steel, welded round pole base,welding standard is according to AWS D 1.1 /BS EN 1011-1,BS EN 1011-2. the entire shaft assembly is hot dipped galvanised according to ASTMA 123 / EN ISO 1461.

Hand hole: 110 by 250mm maintenance opening,complete with cover and ground connector,is centered 300 mm from the bottom of the anchor plate.


Base cover: made of one pieces of fiberglass-reinforced plastics, mechanically assembled together with stainless screws. There is one door in the base cover to access the maintenance opening.

Pole top tenon: high-tensile carbon steel tube,round welded to shaft, standard sizes are 76mm O.D. x 90mm long,special size is available. Finish: "Hot Dip" chemical etching preparation. Polyester powder coat textured finish. Standard colors is black (BK), dark grey(GY) (RAL7016),light grey(LG)(RAL7042),silver grey(SG), White(WH), other colors are available,Durable UV-resistant exterior finish as per # ASTM G7 and outstanding salt-spray resistance according to # ASTM D2247 testing procedures.


Options:

Service hand hole and base plate can be made to specific sizing OEM and ODM is also acceptable

Round base plate



COME WITH 4 ANCHOR BOLTS, 8 NUTS AND 8 WASHERS




ORDERING INFORMATION

Order No.	Install Height meter	D1 Top Diameter (mm)			Base Round x THK(mm)	Anchor Circle Diameter (mm)	Anchor Dia& Length (mm)	Hand hole L x W (mm)	Net Weight (kg)	EPA Rating 80MPA Wall 1/2 (SQ.FT)
PS06B-3.0	3	90	165	3	350x10	215	16x550	250x110	35	41
PS06B-3.5	3.5	90	165	3	350x10	215	16x550	250x110	38	35
PS06B-4.0	4	90	165	3	350x10	215	16x550	250x110	41	29
PS06B-4.5	4.5	90	165	3	350x10	215	16x550	250x110	45	22

Weight without bolts, weight of each bolts is 5kg

Ordering number & sample



PS06B-3.5-BK PS06B-4.0-DB