



**Specifications**

**Application:** Urban roads and street , Squares areas,  
Pedestrian areas, Residential areas,Parks

**Installing Hight:** 3-5m

**Lamps:** LED tube or Fluorescent lamp,70w-150w

**Lamp Wattage**

- 2.5m pole:1800mm light,6\*10W T5 led tube or 6\*21W T5 Fluorescent
- 3m pole:1800mm light,6\*10W T5 led tube or 6\*21W T5 Fluorescent
- 3.5m pole: 2400mm light,6\*15W T5 led tube or 6\*28W T5 Fluorescent
- 4m pole: 2400mm light,6\*15W T5 led tube or 6\*28W T5 Fluorescent

**Input Voltage:** 90-270VAC,50-60HZ or 12V-24VDC

**Material:** Steel body

Lighting Column: Hot dipped galvanized steel, powder coating

Lens: High efficiency acrylic refractor,

Colour: Standard color are Black,Dark grey RAL7016 or  
Light grey RAL 7042,Other colors are available

**Standards:**

Isolation degree Class I, IP Rating IP54



**Ordering Information**

Order No.	Lamp Wattage	Lamp Socket	Install Height	Gross/ Net Weight	Dimension L*W*H(cm)	Packing size(cm)	QTY(pcs) 20'/40'GP
HA0005S-2.5	MAX 150W	G13	2.5m	36/35kg	17X17x250	20x20x250	180/360
HA0005S-3.0	MAX 150W	G13	3m	41/40kg	17X17x300	20x20x300	90/270
HA0005S-3.5	MAX 200W	G13	3.5m	47/46kg	17X17x350	20x20x350	90/270
HA0005-3.0	MAX 150W	G13	3m	57/56kg	22X22x300	24x24x300	70/210
HA0005-3.5	MAX 200W	G13	3.5m	66/65kg	22X22x350	24x24x350	70/210
HA0005-4.0	MAX 200W	G13	4m	74/73kg	22X22x400	24x24x400	70/140