



Specifications

Application: Urban roads and street , Squares areas,
Pedestrian areas, Residential areas,Parks

Installing Hight: 3-5m

Lamps: LED tube or Fluorescent lamp,30w-150w

Lamp Wattage:3m pole:1200mm light ,3*14w T5 led or 3*28w T5 FL
3.5m pole:1200mm light ,3*14w T5 led or 3*28w T5 FL
4.0m pole:1500mm light ,3*17w T5 led or 3*35w T5 FL

Input Voltage: 220-240V/50Hz,110-130V/60Hz

Material: Aluminium body

Lighting Column: Three pieces extrude aluminium assembled trigon column (stripe surface), four aluminium bar supporting lampshade, powder coating

Lens: Clear acrylic /PC lampshade,

Color: Standard color are Black,Dark grey RAL7016 or Light grey RAL 7042 ,other colors are available

Standards:

Isolation degree Class I, IP Rating IP54



Ordering Information

Order No.	Lamp Wattage	Lamp Socket	Install Height	Gross/ Net Weight	Dimension L*W*H(cm)	Packing size(cm)	QTY(pcs) 20'/40'GP
HA0003A1-3.0	T5,LED or FL	G5	3.0m	25/24kg	27x27x300	28x28x300	50/150
HA0003A1-3.5	T5,LED or FL	G5	3.5m	29/28kg	27x27x350	28x28x350	50/150
HA0003A1-4.0	T5,LED or FL	G5	4.0m	33/32kg	27x27x400	28x28x400	50/100
HA0003A2-3.0	T5,LED or FL	G5	3.0m	25/24kg	27x27x300	28x28x300	50/150
HA0003A2-3.5	T5,LED or FL	G5	3.5m	29/28kg	27x27x350	28x28x350	50/150
HA0003A2-4.0	T5,LED or FL	G5	4.0m	33/32kg	27x27x400	28x28x400	50/100